


姿図



品番	LZD-92804YB
光源	LED 14W 3000K
定格光束	660 lm
1/2照度角	39°
ビーム角	42°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.71 H B 0.71 H
保守率	良 0.69
	中 0.67
	否 0.63

反射率 (%)	天井			壁			50			30			0		
	80	70	50	30	10	50	30	10	50	30	10	50	30	10	0
室指数	照 明 率 (× 0.01)														
0.6	84	79	77	83	79	76	82	79	76	82	78	76	75		
0.8	89	85	81	89	84	81	87	84	81	86	83	80	79		
1	94	90	87	94	90	87	92	88	86	90	87	85	83		
1.25	99	94	91	97	94	91	95	92	90	94	91	89	87		
1.5	102	98	95	100	97	94	98	95	93	96	94	92	89		
2	106	103	101	105	102	100	102	100	98	100	98	96	93		
2.5	110	107	105	108	106	104	105	103	102	102	101	99	96		
3	112	110	108	110	108	107	107	106	104	104	103	102	98		
4	114	113	111	112	111	110	109	108	107	105	105	104	100		
5	116	115	114	114	113	112	110	109	108	106	106	105	101		

