


姿図



品番	LZD-60724AW
光源	LED 16W (3500K)
定格光束	810.0 lm
1/2照度角	40°
ビーム角	44°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.73 H B 0.73 H
保守率	良 0.63
	中 0.60
	否 0.53

反射率 (%)	天井		80			70			50			30			0
	壁	床	50	30	10	50	30	10	50	30	10	50	30	10	0
			20			20			20			20			0
室指数	照 明 率 (× 0.01)														
0.6	76	71	67	75	71	67	75	70	67	74	70	67	65		
0.8	82	77	73	82	76	73	80	76	72	79	75	72	70		
1	88	83	79	87	82	79	85	81	78	84	80	77	75		
1.25	93	88	84	92	87	84	90	86	83	88	84	82	79		
1.5	97	92	88	95	91	88	93	89	86	91	88	85	82		
2	102	98	95	101	97	94	98	95	92	95	93	91	88		
2.5	106	103	100	104	101	99	101	99	96	98	96	94	91		
3	109	106	103	107	104	102	103	101	100	100	99	97	93		
4	112	109	107	110	108	106	106	104	103	102	101	100	96		
5	113	112	110	111	110	108	107	106	105	104	103	102	97		

