


姿図



品 番	LZD-92282AWV
光 源	LED 15W Q+3500K
定格光束	1020.0 lm
1/2照度角	53 °
ビーム角	64 °

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.99 H B 0.99 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (×0.01)												
0.6		78	74	70	78	73	70	77	73	70	76	72	70	68
0.8		85	80	76	84	80	76	83	79	76	82	78	75	74
1		91	86	83	90	86	82	88	85	82	87	83	81	79
1.25		96	91	88	95	91	87	93	89	86	91	88	85	83
1.5		99	95	92	98	94	91	96	92	90	94	91	89	86
2		105	101	98	103	100	97	100	98	96	98	96	94	91
2.5		108	105	103	106	104	102	103	101	99	100	99	97	94
3		111	108	106	109	107	105	105	104	102	102	101	100	96
4		113	111	109	111	109	108	107	106	105	104	103	102	98
5		115	113	112	112	111	110	109	108	107	105	104	103	99

