


姿図



品番	DCL-40457W
光源	LED 6.5W 5000K
定格光束	470 lm
1/2照度角	64°
ビーム角	106°

器具効率	100.0 %
上方光束	0.1 %
下方光束	99.9 %
器具間隔 最大限 (取付高さH)	A 1.24 H
	B 1.24 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6	47	39	33	46	38	33	45	38	33	44	37	33	31	
0.8	57	48	42	56	48	42	54	47	41	53	46	41	39	
1	65	56	50	64	56	50	62	55	49	60	54	49	46	
1.25	73	64	58	72	64	58	69	62	57	67	61	56	53	
1.5	79	71	64	77	70	64	75	68	63	72	66	62	59	
2	87	80	75	86	79	74	83	77	72	80	75	71	67	
2.5	93	87	82	91	85	81	88	83	79	85	80	77	73	
3	97	92	87	95	90	86	91	87	83	88	85	81	77	
4	102	98	93	100	96	92	96	93	89	92	90	87	83	
5	105	101	98	103	100	96	99	96	93	95	93	90	86	

