


姿図



品 番	DPN-38290Y
光 源	LDA5L-G/40W/B27K x4 <DAIKO>
定格光束	2000 lm
1/2照度角	79°
ビーム角	360°

器具効率	86.5 %
上方光束	40.9 %
下方光束	45.5 %
器具間隔 最大限 (取付高さH)	A 1.64 H B 1.64 H
保 守 率	良 0.63 中 0.60 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		29	22	17	27	20	16	23	17	13	19	14	11	7
0.8		36	29	23	34	26	21	28	22	18	23	18	15	9
1		42	34	28	39	32	26	32	27	22	26	22	18	11
1.25		48	40	34	44	37	31	37	31	27	30	26	22	14
1.5		53	45	39	48	41	36	40	35	30	33	29	25	16
2		60	52	46	55	48	43	46	41	36	37	33	30	20
2.5		64	57	52	59	53	48	49	45	41	40	37	34	23
3		68	61	56	62	57	52	52	48	44	43	39	36	25
4		73	67	62	67	62	58	56	52	49	46	43	41	28
5		76	71	66	70	65	62	58	55	52	48	46	43	30

