


姿図



品番	DPN-38289Y
光源	LDA5L-G/40W/B27K x3 <DAIKO>
定格光束	1500 lm
1/2照度角	80°
ビーム角	322°

器具効率	86.2 %
上方光束	38.3 %
下方光束	47.9 %
器具間隔 最大限 (取付高さH)	A 1.68 H
	B 1.68 H
保守率	良 0.63
	中 0.60
	否 0.56

反射率 (%)	天井			70			50			30			0	
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床			20			20			20			0	
室指数	照 明 率 ( × 0.01 )													
0.6	29	22	17	27	20	16	23	17	13	19	14	11	7	
0.8	36	28	23	34	26	21	28	22	18	23	19	15	10	
1	42	34	28	39	32	26	33	27	22	27	22	19	12	
1.25	48	40	34	44	37	31	37	31	27	31	26	22	15	
1.5	53	45	38	48	41	36	41	35	30	34	29	26	17	
2	59	52	46	55	48	43	46	41	37	38	34	31	21	
2.5	64	57	51	59	53	48	50	45	41	41	38	34	24	
3	68	61	56	63	57	52	53	48	44	44	40	37	26	
4	73	67	62	67	62	58	57	53	49	47	44	42	30	
5	76	71	66	70	66	62	59	56	53	49	47	44	32	

