


姿図



品 番	DSL-5323AW_1灯
光 源	LED8.1W 3500K
定格光束	750.0 lm
1/2照度角	66°
ビーム角	84°

器具効率	100.0 %
上方光束	18.0 %
下方光束	82.0 %
器具間隔 最大限 (取付高さH)	A 1.29 H B 1.29 H
保 守 率	良 0.69 中 0.67 否 0.63

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		48	40	35	47	39	34	44	38	33	41	36	32	29
0.8		56	48	42	55	47	42	51	45	40	48	42	38	34
1		63	55	49	61	54	48	57	51	46	53	48	44	39
1.25		70	62	56	68	60	54	63	57	52	59	53	49	44
1.5		75	67	61	73	65	60	67	61	57	63	58	54	48
2		83	76	70	80	73	68	74	69	64	68	64	60	54
2.5		88	81	76	85	79	74	78	73	69	72	69	65	58
3		92	86	81	88	83	78	81	77	73	75	72	69	61
4		96	91	87	93	88	84	85	82	79	79	76	73	65
5		99	95	91	95	92	88	88	85	82	81	79	76	68

