


姿図



| | |
|--------|---------------|
| 品番 | DSL-5325WW |
| 光源 | LED8.1W 5000K |
| 定格光束 | 610.0 lm |
| 1/2照度角 | 59° |
| ビーム角 | 88° |

| | |
|------------------------|----------|
| 器具効率 | 100.0 % |
| 上方光束 | 0.0 % |
| 下方光束 | 100.0 % |
| 器具間隔 最大限 (取付高さH) | A 1.14 H |
| | B 1.14 H |
| 保守率 | 良 0.69 |
| | 中 0.67 |
| | 否 0.63 |

| 反射率 (%) | 天井 | 80 | | | 70 | | | 50 | | | 30 | | | 0 |
|---------|----|------------------|-----|-----|-----|-----|-----|-----|-----|----|----|----|----|----|
| | 壁 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| | 床 | 20 | | | 20 | | | 20 | | | 20 | | | 0 |
| 室指数 | | 照 明 率 (× 0.01) | | | | | | | | | | | | |
| 0.6 | | 55 | 47 | 42 | 54 | 47 | 42 | 53 | 46 | 42 | 52 | 46 | 42 | 40 |
| 0.8 | | 65 | 57 | 52 | 64 | 57 | 52 | 63 | 56 | 51 | 61 | 55 | 51 | 49 |
| 1 | | 73 | 66 | 60 | 72 | 65 | 60 | 70 | 64 | 60 | 69 | 63 | 59 | 57 |
| 1.25 | | 81 | 74 | 69 | 80 | 73 | 68 | 77 | 72 | 67 | 75 | 70 | 66 | 64 |
| 1.5 | | 86 | 80 | 75 | 85 | 79 | 74 | 83 | 77 | 73 | 80 | 76 | 72 | 69 |
| 2 | | 94 | 89 | 84 | 93 | 88 | 83 | 90 | 85 | 82 | 87 | 83 | 80 | 77 |
| 2.5 | | 99 | 94 | 90 | 97 | 93 | 89 | 94 | 90 | 87 | 91 | 88 | 85 | 82 |
| 3 | | 103 | 98 | 95 | 101 | 97 | 93 | 97 | 94 | 91 | 94 | 91 | 89 | 85 |
| 4 | | 106 | 103 | 100 | 104 | 101 | 98 | 101 | 98 | 96 | 97 | 95 | 93 | 89 |
| 5 | | 109 | 106 | 103 | 107 | 104 | 101 | 103 | 100 | 98 | 99 | 97 | 95 | 91 |

