


姿図



品 番	DCL-40457A
光 源	LED 6.5W 3500K Ra96
定格光束	500.0 lm
1/2照度角	65 °
ビーム角	110 °

器具効率	100.0 %
上方光束	0.2 %
下方光束	99.8 %
器具間隔 最大限 (取付高さ H)	A 1.27 H B 1.27 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		47	38	33	46	38	33	45	38	32	44	37	32	30
0.8		57	48	42	56	48	42	54	47	41	52	46	41	39
1		65	56	50	64	56	50	62	55	49	60	53	48	46
1.25		73	64	58	71	64	58	69	62	57	67	61	56	53
1.5		79	71	64	77	70	64	74	68	63	72	66	62	59
2		87	80	75	86	79	74	82	77	72	80	75	71	67
2.5		93	87	82	91	85	81	88	83	79	84	80	77	73
3		97	92	87	95	90	86	91	87	83	88	85	81	77
4		102	98	94	100	96	92	96	93	89	92	89	87	82
5		105	101	98	103	100	96	99	96	93	95	93	90	86

