


姿図



品 番

LZW-60716YS

光 源

LED 46W (3000K)

定格光束

3220.0 lm

1/2照度角

35°

ビーム角

38°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %

器具間隔 最大限 (取付高さH)	A 0.64 H
	B 0.64 H

保 守 率	良	0.67
	中	0.63
	否	0.60

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		76	71	67	75	70	67	74	70	67	73	69	67	65
0.8		83	77	74	82	77	73	81	76	73	79	75	72	71
1		89	84	80	88	83	79	86	82	79	85	81	78	76
1.25		94	89	85	93	88	85	91	87	84	89	85	83	81
1.5		97	93	89	96	92	89	94	90	88	92	89	86	84
2		103	99	96	102	98	95	99	96	94	96	94	92	89
2.5		107	104	101	105	102	100	102	100	98	99	97	96	92
3		109	107	104	108	105	103	104	102	101	101	100	98	95
4		112	110	108	110	108	107	106	105	104	103	102	101	97
5		114	112	111	112	110	109	108	107	105	104	103	102	98

