


姿図



品 番	LLS-7002WUME
光 源	LED 6.1W 5000K
定格光束	310.0 lm
1/2照度角	14°
ビーム角	14°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.25 H B 0.23 H
保 守 率	良 0.69 中 0.67 否 0.63

反射率(%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		84	79	76	83	79	76	82	79	76	82	78	76	74
0.8		89	85	81	89	84	81	87	83	81	86	83	80	79
1		95	90	87	94	90	87	92	89	86	91	88	85	83
1.25		99	95	91	98	94	91	96	93	90	94	91	89	87
1.5		102	98	95	101	97	94	99	96	93	96	94	92	89
2		107	104	101	106	103	100	103	100	98	100	98	97	93
2.5		110	108	105	109	106	104	106	104	102	103	101	100	96
3		113	111	109	111	109	107	108	106	105	105	103	102	99
4		115	114	112	113	112	110	110	108	107	106	105	105	100
5		117	116	114	115	114	113	111	110	109	107	107	106	101

