


姿図



品番	DSL-5327AB
光源	LED8.1W 3500K
定格光束	470.0 lm
1/2照度角	58°
ビーム角	82°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.11 H B 1.11 H
保守率	良 0.69
	中 0.67
	否 0.63

反射率 (%)	天井				70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床				20			20			20			0
室指数	照 明 率 ( × 0.01 )													
0.6	59	52	47	58	52	47	57	51	47	56	51	47	45	
0.8	69	62	57	68	62	57	67	61	56	65	60	56	54	
1	77	70	65	76	70	65	74	69	64	73	68	64	62	
1.25	85	78	73	83	77	73	81	76	72	79	75	71	69	
1.5	90	84	79	88	83	79	86	81	77	84	80	76	73	
2	97	92	88	96	91	87	93	89	85	90	87	84	81	
2.5	102	97	94	100	96	92	97	93	90	94	91	88	85	
3	105	101	98	103	99	96	99	97	94	96	94	92	88	
4	108	105	102	106	103	101	102	100	98	99	97	95	91	
5	110	107	105	108	106	103	104	102	100	100	99	97	93	

