


姿図



品 番	DCL-40033W
光 源	LED 6.1W 5000K
定格光束	540 lm
1/2照度角	62°
ビーム角	102°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.20 H B 1.21 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		48	40	34	47	40	34	46	39	34	45	38	34	32
0.8		58	50	43	57	49	43	55	48	43	54	47	43	40
1		66	58	51	65	57	51	63	56	51	61	55	50	48
1.25		74	66	60	73	65	59	70	64	58	68	62	58	55
1.5		80	72	66	78	71	65	76	70	64	73	68	63	60
2		89	82	76	87	80	75	84	78	74	81	76	72	69
2.5		94	88	83	92	87	82	89	84	80	86	82	78	75
3		98	93	88	96	91	87	92	88	85	89	86	83	79
4		103	99	95	101	97	93	97	94	91	93	90	88	84
5		106	102	99	104	100	97	100	97	94	96	93	91	87

