


姿図



品 番	DDL-4496AB
光 源	LED 7.7W 3500K
定格光束	440.0 lm
1/2照度角	(A29° A' 29°) B-B' 59°
ビーム角	(A44° A' 39°) B-B' 88°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A *** H B 1.14 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		56	48	43	55	48	43	54	47	43	53	47	43	41
0.8		66	59	53	65	58	53	64	58	53	62	57	52	50
1		75	67	62	74	67	62	72	66	61	70	65	61	58
1.25		82	76	70	81	75	70	79	73	69	77	72	68	66
1.5		88	81	76	86	81	76	84	79	75	81	77	74	71
2		95	90	86	94	89	85	91	87	83	88	85	82	78
2.5		100	95	92	98	94	90	95	92	88	92	89	87	83
3		103	99	96	102	98	95	98	95	92	95	92	90	86
4		107	104	101	105	102	99	101	99	96	98	96	94	90
5		109	106	104	107	105	102	103	101	99	99	98	96	91

