


姿図



品 番	DSL-4781AW
光 源	LED8W 3500K
定格光束	890.0 lm
1/2照度角	32°
ビーム角	34°

器具効率	100.0 %	反射率 (%)	天井	80			70			50			30			0
			壁	50	30	10	50	30	10	50	30	10	50	30	10	0
上方光束	0.0 %		床	20			20			20			20			0
下方光束	100.0 %		室指数	照 明 率 (× 0.01)												
器具間隔 最大限 (取付高さH)	A	0.57 H	0.6	81	76	73	80	76	73	79	75	72	78	75	72	71
	B	0.57 H	0.8	87	82	78	86	81	78	84	80	77	83	80	77	75
			1	92	87	84	91	87	84	90	86	83	88	85	82	80
			1.25	97	92	89	96	91	88	93	90	87	92	89	86	84
保 守 率	良 中 否	0.63 0.60 0.56	1.5	100	96	93	99	95	92	96	93	91	94	92	89	87
			2	105	102	99	104	100	98	101	98	96	98	96	94	91
			2.5	109	106	103	107	104	102	104	102	100	101	99	98	94
			3	111	109	107	109	107	105	106	104	103	103	102	100	97
			4	114	112	110	112	110	109	108	107	106	104	104	103	98
			5	115	114	112	113	112	111	109	108	107	105	105	104	100

