


姿図



品 番	DDL-5362YB
光 源	LED7.6W 2700K
定格光束	520.0 lm
1/2照度角	61°
ビーム角	94°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.18 H B 1.18 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		53	45	40	52	45	40	51	45	40	50	44	40	38
0.8		64	56	50	63	55	50	61	54	50	60	54	49	47
1		72	64	59	71	64	58	69	63	58	67	62	57	55
1.25		80	73	67	79	72	67	76	70	66	74	69	65	62
1.5		85	79	73	84	78	73	81	76	72	79	74	71	68
2		94	88	83	92	87	82	89	84	81	86	82	79	76
2.5		99	94	89	97	92	88	93	90	86	90	87	84	81
3		102	98	94	100	96	93	97	93	91	93	91	88	84
4		106	103	100	104	101	98	100	98	95	97	95	93	88
5		109	106	103	107	104	101	102	100	98	99	97	95	91

