


姿図



品番	DOL-5349YB
光源	LED4.1W 2700K
定格光束	260.0 lm
1/2照度角	20°
ビーム角	20°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.35 H B 0.35 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
床	20			20			20			20			0	
室指数	照 明 率 ( × 0.01 )													
0.6	81	76	73	80	76	73	79	75	72	79	75	72	71	
0.8	87	82	78	86	82	78	85	81	78	84	80	77	76	
1	93	88	84	92	87	84	90	86	83	88	85	83	81	
1.25	97	93	89	96	92	89	94	90	88	92	89	87	84	
1.5	101	96	93	99	95	92	97	94	91	95	92	90	87	
2	106	102	99	104	101	98	101	99	97	99	97	95	92	
2.5	109	106	104	108	105	103	104	102	101	102	100	98	95	
3	112	109	107	110	108	106	107	105	103	104	102	101	97	
4	114	113	111	112	111	109	109	107	106	105	104	103	99	
5	116	115	113	114	113	111	110	109	108	106	106	105	100	

