


姿図



品番	DDL-5011WTG
光源	LED 5.8W 5000K
定格光束	480.0 lm
1/2照度角	62°
ビーム角	94°

器具効率	99.7 %
上方光束	0.0 %
下方光束	99.7 %
器具間隔 最大限 (取付高さH)	A 1.21 H
	B 1.21 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井			壁			50			30			0		
	80	70	50	30	10	50	30	10	50	30	10	50	30	10	0
	20			20			20			20			0		
室指数	照 明 率 (× 0.01)														
0.6	54	46	41	53	46	41	52	45	41	51	45	40	38		
0.8	64	56	51	63	56	51	62	55	50	60	54	50	48		
1	72	65	59	71	64	59	69	63	58	68	62	58	55		
1.25	80	73	68	79	72	67	77	71	66	74	69	65	63		
1.5	86	79	74	84	78	73	82	76	72	79	75	71	68		
2	94	88	83	92	87	82	89	85	81	86	82	79	76		
2.5	99	94	89	97	92	88	93	90	86	90	87	84	81		
3	102	98	94	100	96	93	97	93	90	93	91	88	84		
4	106	102	99	104	101	98	100	97	95	96	94	92	88		
5	108	105	103	106	103	101	102	100	98	98	97	95	90		

