


姿図



品番	DSL-5326AWG
光源	LED8.5W 3500K
定格光束	600.0 lm
1/2照度角	59°
ビーム角	88°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.14 H B 1.14 H
保守率	良 0.69
	中 0.67
	否 0.63

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	55	47	42	54	47	42	53	46	42	52	46	42	40	
0.8	65	57	52	64	57	52	63	56	51	61	55	51	49	
1	73	66	60	72	65	60	70	64	60	69	63	59	57	
1.25	81	74	69	80	73	68	77	72	67	75	70	66	64	
1.5	86	80	75	85	79	74	83	77	73	80	76	72	69	
2	94	89	84	93	88	83	90	85	82	87	83	80	77	
2.5	99	94	90	97	93	89	94	90	87	91	88	85	82	
3	103	98	95	101	97	93	97	94	91	94	91	89	85	
4	106	103	100	104	101	98	101	98	96	97	95	93	89	
5	109	106	103	107	104	101	103	100	98	99	97	95	91	

