


姿図



品番	DDL-4094WWG
光源	LED 5.8W 5000K
定格光束	360.0 lm
1/2照度角	21°
ビーム角	22°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.37 H B 0.37 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井			壁			50			30			0		
	80	70	50	50	30	10	50	30	10	50	30	10	50	30	10
床	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20
室指数	照 明 率 (× 0.01)														
0.6	81	77	74	81	76	73	80	76	73	79	75	73	72		
0.8	87	82	79	86	82	79	85	81	78	84	80	78	76		
1	92	88	85	92	87	84	90	86	83	88	85	83	81		
1.25	97	93	89	96	92	89	94	90	88	92	89	87	85		
1.5	100	96	93	99	95	92	97	93	91	94	92	90	87		
2	105	102	99	104	101	98	101	98	96	98	96	95	92		
2.5	109	106	103	107	104	102	104	102	100	101	99	98	95		
3	111	109	107	109	107	105	106	104	103	103	102	101	97		
4	113	112	110	111	110	109	108	107	106	104	104	103	99		
5	115	114	112	113	112	111	109	108	107	105	105	104	100		

