


姿図



品 番	DSL-5422ABG
光 源	LED 8.5W 3500K
定格光束	650 lm
1/2照度角	20°
ビーム角	20°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.35 H B 0.35 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		81	77	73	81	76	73	80	76	73	79	75	73	71
0.8		87	82	79	87	82	79	85	81	78	84	81	78	76
1		93	88	85	92	88	85	90	87	84	89	86	83	81
1.25		97	93	90	96	92	89	94	91	88	92	90	87	85
1.5		101	97	93	100	96	93	97	94	92	95	92	90	88
2		106	103	100	104	101	99	102	99	97	99	97	95	92
2.5		109	107	104	108	105	103	105	103	101	102	100	99	95
3		112	109	107	110	108	106	107	105	104	104	102	101	97
4		114	112	111	112	111	109	109	107	106	105	104	103	99
5		116	114	113	114	112	111	110	109	108	106	105	105	100

