


姿図



品番	DSL-4720FWG
光源	LED 8W 5000K-2700K
定格光束	405 lm
1/2照度角	63°
ビーム角	94°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.23 H B 1.23 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井		80			70			50			30			0
	壁	床	50	30	10	50	30	10	50	30	10	50	30	10	0
			20		20			20			20			0	
室指数	照 明 率 (× 0.01)														
0.6	55	47	42	54	47	42	53	46	42	52	46	42	40		
0.8	65	57	52	64	57	52	63	56	51	61	55	51	49		
1	73	66	60	72	65	60	70	64	60	69	63	59	57		
1.25	81	74	68	80	73	68	77	72	67	75	70	66	64		
1.5	86	80	74	85	79	74	82	77	73	80	75	72	69		
2	94	88	84	92	87	83	89	85	81	87	83	80	76		
2.5	99	94	90	97	92	89	94	90	87	91	88	85	81		
3	102	98	94	100	96	93	97	93	91	93	91	88	84		
4	106	102	99	104	101	98	100	97	95	96	94	92	88		
5	108	105	102	106	103	101	102	100	98	98	96	95	90		

