


姿図



品番	DDL-4920YBG
光源	LED 13.4W 2700K
定格光束	1080 lm
1/2照度角	64°
ビーム角	96°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.24 H
	B 1.24 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井				壁				床				
	80	70	50	30	80	70	50	30	80	70	50	30	
室指数	照明率 (×0.01)												
0.6	53	46	40	53	45	40	51	45	40	50	44	40	38
0.8	64	56	50	63	56	50	61	55	50	60	54	49	47
1	72	65	59	71	64	59	69	63	58	67	62	58	55
1.25	80	73	67	79	72	67	77	71	66	74	69	65	63
1.5	86	79	74	84	78	73	82	76	72	79	75	71	68
2	94	88	83	92	87	82	89	85	81	86	83	79	76
2.5	99	94	89	97	92	88	94	90	86	90	87	85	81
3	102	98	94	100	96	93	97	93	91	93	91	88	84
4	106	103	99	104	101	98	100	98	95	97	95	93	88
5	109	106	103	106	104	101	102	100	98	99	97	95	90

