


姿図



品番	DSL-4716FWG
光源	LED 8W 5000K-2700K
定格光束	700 lm
1/2照度角	65°
ビーム角	90°

器具効率	100.0 %
上方光束	12.6 %
下方光束	87.4 %
器具間隔 最大限 (取付高さH)	A 1.28 H B 1.28 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	49	41	36	48	40	35	45	39	34	43	38	34	31	
0.8	58	50	44	56	49	43	53	47	42	51	45	41	37	
1	65	57	51	63	56	50	60	53	48	57	51	47	43	
1.25	72	64	58	70	63	57	66	60	55	62	57	53	48	
1.5	77	70	64	75	68	62	71	65	60	67	62	58	53	
2	85	78	73	82	76	71	77	72	68	73	68	65	59	
2.5	90	84	79	87	82	77	82	77	73	77	73	70	64	
3	94	88	83	91	86	81	85	81	77	80	76	73	67	
4	99	94	90	95	91	87	89	86	82	83	80	78	71	
5	101	97	94	98	94	91	91	88	86	85	83	81	73	

