


姿図



品番	LZD-93108AWN
光源	LED 10.6W 3500K
定格光束	210 lm
1/2照度角	16°
ビーム角	17°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.28 H B
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 ( × 0.01 )													
0.6	83	78	75	83	78	75	82	78	75	81	77	75	73	
0.8	89	84	81	88	84	80	87	83	80	85	82	79	78	
1	94	90	86	93	89	86	92	88	85	90	87	84	83	
1.25	98	94	91	97	93	90	95	92	89	93	91	88	86	
1.5	102	98	94	100	97	94	98	95	92	96	93	91	89	
2	107	103	101	105	102	100	102	100	98	100	98	96	93	
2.5	110	107	105	108	106	104	105	103	101	102	101	99	96	
3	112	110	108	111	109	107	107	106	104	104	103	102	98	
4	115	113	112	113	111	110	109	108	107	106	105	104	100	
5	116	115	114	114	113	112	110	109	109	107	106	105	101	

