


姿図



品番	LZD-93108RBM
光源	LED 10.6W 2500K
定格光束	290 lm
1/2照度角	23°
ビーム角	26°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.41 H B
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井			壁			50			30			0		
	80	70	50	50	30	10	50	30	10	50	30	10	50	30	10
床	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20
室指数	照 明 率 ( × 0.01 )														
0.6	83	79	76	83	79	76	82	78	75	81	78	75	74		
0.8	89	84	81	88	84	81	87	83	80	86	82	80	78		
1	94	90	86	93	89	86	92	88	85	90	87	85	83		
1.25	98	94	91	97	93	90	95	92	89	93	91	88	86		
1.5	101	98	95	100	97	94	98	95	93	96	93	91	89		
2	106	103	100	105	102	100	102	100	98	100	98	96	93		
2.5	110	107	105	108	106	104	105	103	101	102	101	99	96		
3	112	110	108	110	108	107	107	106	104	104	103	102	98		
4	115	113	111	113	111	110	109	108	107	105	105	104	100		
5	116	115	114	114	113	112	110	109	108	106	106	105	101		

