

姿図



品 番	LZD-90628XW+LZA-93096WWM
光 源	DECO-S Lite 4.3W 5000K M
定格光束	515 lm
1/2照度角	22°
ビーム角	22°

器具効率	80.2 %
上方光束	0.0 %
下方光束	80.2 %
器具間隔 最大限 (取付高さH)	A 0.39 H
保 守 率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		66	62	60	65	62	60	65	62	59	64	61	59	58
0.8		70	66	64	70	66	64	69	66	63	68	65	63	62
1		74	71	68	74	70	68	72	70	67	71	69	67	65
1.25		78	74	72	77	74	71	75	73	71	74	72	70	68
1.5		80	77	75	79	76	74	78	75	73	76	74	72	70
2		84	82	80	83	81	79	81	79	77	79	77	76	74
2.5		87	85	83	86	84	82	83	82	80	81	80	79	76
3		89	87	86	88	86	85	85	84	83	83	82	81	78
4		91	90	88	89	88	87	86	86	85	84	83	82	79
5		92	91	90	91	90	89	87	87	86	85	84	84	80

