


姿図



品番	LZW-60712NSE
光源	LED 4000K 21W
定格光束	1960 lm
1/2照度角	35°
ビーム角	38°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.64 H B 0.64 H
保守率	良 0.69
	中 0.67
	否 0.63

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
床	20													
室指数	照 明 率 ( × 0.01 )													
0.6	76	71	68	76	71	68	75	70	67	74	70	67	66	
0.8	83	78	74	82	77	74	81	77	73	80	76	73	71	
1	89	84	80	88	84	80	87	82	79	85	81	79	77	
1.25	94	89	86	93	89	85	91	87	84	89	86	83	81	
1.5	98	93	90	97	93	89	94	91	88	92	89	87	84	
2	104	100	97	102	99	96	99	96	94	97	94	92	89	
2.5	107	104	101	106	103	100	102	100	98	99	98	96	93	
3	110	107	105	108	106	104	105	103	101	102	100	99	95	
4	112	110	109	110	109	107	107	105	104	103	102	101	97	
5	114	112	111	112	111	109	108	107	106	104	104	103	98	

