

姿図



品 番

LZW-92353XB+LZA-93096YBW

光 源

DECO-S Lite 4.3W 3000K W

定格光束

500 lm

1/2照度角

29°

ビーム角

31°

|      |        |
|------|--------|
| 器具効率 | 86.5 % |
| 上方光束 | 0.0 %  |
| 下方光束 | 86.5 % |

|                        |          |
|------------------------|----------|
| 器具間隔<br>最大限<br>(取付高さH) | A 0.53 H |
|                        | B 0.53 H |

|       |   |      |
|-------|---|------|
| 保 守 率 | 良 | 0.69 |
|       | 中 | 0.67 |
|       | 否 | 0.63 |

| 反射率<br>(%) | 天井 | 80               |    |    | 70 |    |    | 50 |    |    | 30 |    |    | 0  |
|------------|----|------------------|----|----|----|----|----|----|----|----|----|----|----|----|
|            | 壁  | 50               | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0  |
|            | 床  | 20               |    |    | 20 |    |    | 20 |    |    | 20 |    |    | 0  |
| 室指数        |    | 照 明 率 ( × 0.01 ) |    |    |    |    |    |    |    |    |    |    |    |    |
| 0.6        |    | 72               | 68 | 66 | 72 | 68 | 66 | 71 | 68 | 66 | 70 | 67 | 65 | 64 |
| 0.8        |    | 77               | 73 | 70 | 76 | 73 | 70 | 75 | 72 | 70 | 74 | 71 | 69 | 68 |
| 1          |    | 81               | 78 | 75 | 81 | 77 | 75 | 79 | 76 | 74 | 78 | 75 | 73 | 72 |
| 1.25       |    | 85               | 81 | 79 | 84 | 81 | 78 | 82 | 80 | 77 | 81 | 78 | 77 | 75 |
| 1.5        |    | 88               | 84 | 82 | 87 | 84 | 81 | 85 | 82 | 80 | 83 | 81 | 79 | 77 |
| 2          |    | 92               | 89 | 87 | 91 | 88 | 86 | 88 | 86 | 84 | 86 | 84 | 83 | 80 |
| 2.5        |    | 95               | 92 | 90 | 93 | 91 | 89 | 91 | 89 | 88 | 88 | 87 | 86 | 83 |
| 3          |    | 97               | 95 | 93 | 95 | 93 | 92 | 92 | 91 | 90 | 90 | 89 | 88 | 85 |
| 4          |    | 99               | 97 | 96 | 97 | 96 | 95 | 94 | 93 | 92 | 91 | 90 | 90 | 86 |
| 5          |    | 100              | 99 | 98 | 98 | 97 | 96 | 95 | 94 | 93 | 92 | 91 | 91 | 87 |

