


姿図



品 番	LZD-93125DWW+LZA-93313+LZA-93015
光 源	LED 30W Q+4000K
定格光束	1600 lm
1/2照度角	49°
ビーム角	62°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.91 H
保 守 率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		70	64	60	69	64	60	68	63	60	67	63	59	58
0.8		78	72	68	77	72	68	76	71	67	74	70	67	65
1		85	79	75	84	79	75	82	78	74	81	77	73	71
1.25		91	86	82	90	85	81	88	83	80	86	82	79	77
1.5		95	90	86	94	89	86	91	88	84	89	86	83	81
2		101	97	94	100	96	93	97	94	91	94	92	90	86
2.5		105	102	99	104	100	98	100	98	96	97	95	94	90
3		108	105	102	106	104	101	103	101	99	100	98	96	93
4		111	108	106	109	107	105	105	103	102	102	100	99	95
5		113	111	109	110	109	107	107	105	104	103	102	101	96

