


姿図



品番	LZW-60711YSE
光源	LED 3000K 21W
定格光束	1890 lm
1/2照度角	11°
ビーム角	12°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.20 H B 0.20 H
保守率	良 0.69
	中 0.67
	否 0.63

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	81	76	73	80	76	73	79	75	72	79	75	72	71	
0.8	87	82	78	86	82	78	85	81	78	84	80	77	75	
1	93	88	84	92	87	84	90	86	83	89	85	82	81	
1.25	97	93	89	96	92	89	94	91	88	92	89	87	84	
1.5	101	97	93	100	96	92	97	94	91	95	92	90	87	
2	106	103	100	105	101	99	102	99	97	99	97	95	92	
2.5	110	107	104	108	105	103	105	103	101	102	100	99	95	
3	112	110	108	111	108	106	107	105	104	104	103	101	98	
4	115	113	111	113	111	110	109	108	107	106	105	104	100	
5	117	115	114	115	113	112	111	110	109	107	106	106	101	

