


姿図



品 番	LZD-93125EWN+LZA-93015
光 源	LED 30W Q+3500K
定格光束	1880 lm
1/2照度角	11°
ビーム角	11°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.19 H
保 守 率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	86	81	78	85	81	78	85	81	78	84	80	78	76	
0.8	92	87	84	91	86	83	90	86	83	88	85	82	81	
1	97	93	89	96	92	89	94	91	88	93	90	87	85	
1.25	101	97	94	100	96	93	98	95	92	96	93	91	89	
1.5	105	101	97	103	100	97	101	98	95	99	96	94	92	
2	110	106	104	108	105	103	105	103	101	103	101	99	96	
2.5	113	110	108	111	109	107	108	106	104	105	104	102	99	
3	115	113	111	114	112	110	110	109	107	107	106	105	101	
4	118	116	115	116	114	113	112	111	110	108	108	107	103	
5	119	118	117	117	116	115	113	112	112	109	109	108	104	

