


姿図



品番	LZD-93124GWW+LZA-93014
光源	LED 22.6W Q+3000K
定格光束	1000 lm
1/2照度角	30°
ビーム角	32°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.54 H B
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
		壁	50	30	10	50	30	10	50	30	10	50	30	10
	床	20			20			20			20			0
室指数		照 明 率 ( × 0.01 )												
0.6	82	78	75	82	78	75	81	77	74	80	77	74	73	
0.8	88	83	80	87	83	80	86	82	79	85	82	79	77	
1	94	89	86	93	89	85	91	88	85	90	86	84	82	
1.25	98	94	91	97	93	90	95	92	89	93	90	88	86	
1.5	101	97	94	100	96	93	98	95	92	96	93	91	88	
2	106	103	100	105	102	99	102	100	98	99	97	96	93	
2.5	110	107	105	108	106	103	105	103	101	102	100	99	96	
3	112	110	108	110	108	107	107	105	104	104	103	102	98	
4	114	113	111	113	111	110	109	108	107	105	105	104	100	
5	116	115	113	114	113	112	110	109	108	106	106	105	101	

