

姿図



品 番

LZD-90628XB+LZA-93096WWW

光 源

DECO-S Lite 4.3W 5000K W

定格光束

525 lm

1/2照度角

26°

ビーム角

28°

|                        |   |        |
|------------------------|---|--------|
| 器具効率                   |   | 78.1 % |
| 上方光束                   |   | 0.0 %  |
| 下方光束                   |   | 78.1 % |
| 器具間隔<br>最大限<br>(取付高さH) | A | 0.46 H |
|                        | B | 0.46 H |
| 保 守 率                  | 良 | 0.67   |
|                        | 中 | 0.63   |
|                        | 否 | 0.56   |

| 反射率<br>(%) | 天井 | 80               |    |    | 70 |    |    | 50 |    |    | 30 |    |    | 0  |
|------------|----|------------------|----|----|----|----|----|----|----|----|----|----|----|----|
|            | 壁  | 50               | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0  |
|            | 床  | 20               |    |    | 20 |    |    | 20 |    |    | 20 |    |    | 0  |
| 室指数        |    | 照 明 率 ( × 0.01 ) |    |    |    |    |    |    |    |    |    |    |    |    |
| 0.6        |    | 64               | 61 | 58 | 64 | 61 | 58 | 63 | 60 | 58 | 63 | 60 | 58 | 57 |
| 0.8        |    | 69               | 65 | 62 | 68 | 65 | 62 | 67 | 64 | 62 | 66 | 63 | 61 | 60 |
| 1          |    | 73               | 69 | 67 | 72 | 69 | 66 | 71 | 68 | 66 | 70 | 67 | 65 | 64 |
| 1.25       |    | 76               | 73 | 70 | 75 | 72 | 70 | 74 | 71 | 69 | 72 | 70 | 68 | 67 |
| 1.5        |    | 79               | 75 | 73 | 78 | 75 | 72 | 76 | 73 | 71 | 74 | 72 | 71 | 69 |
| 2          |    | 82               | 80 | 78 | 81 | 79 | 77 | 79 | 77 | 76 | 77 | 76 | 74 | 72 |
| 2.5        |    | 85               | 83 | 81 | 84 | 82 | 80 | 81 | 80 | 78 | 79 | 78 | 77 | 74 |
| 3          |    | 87               | 85 | 84 | 86 | 84 | 83 | 83 | 82 | 81 | 81 | 80 | 79 | 76 |
| 4          |    | 89               | 87 | 86 | 87 | 86 | 85 | 84 | 83 | 83 | 82 | 81 | 80 | 77 |
| 5          |    | 90               | 89 | 88 | 88 | 87 | 87 | 85 | 85 | 84 | 82 | 82 | 82 | 78 |

