

姿図



品 番	LZD-90628XW+LZA-93096CWW
光 源	DECO-S Lite 4.3W 2200K W
定格光束	425 lm
1/2照度角	26°
ビーム角	28°

器具効率	78.1 %
上方光束	0.0 %
下方光束	78.1 %
器具間隔 最大限 (取付高さH)	A 0.46 H B 0.46 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		64	61	58	64	61	58	63	60	58	63	60	58	57
0.8		69	65	62	68	65	62	67	64	62	66	63	61	60
1		73	69	67	72	69	66	71	68	66	70	67	65	64
1.25		76	73	70	75	72	70	74	71	69	72	70	68	67
1.5		79	75	73	78	75	72	76	73	71	74	72	71	69
2		82	80	78	81	79	77	79	77	76	77	76	74	72
2.5		85	83	81	84	82	80	81	80	78	79	78	77	74
3		87	85	84	86	84	83	83	82	81	81	80	79	76
4		89	87	86	87	86	85	84	83	83	82	81	80	77
5		90	89	88	88	87	87	85	85	84	82	82	82	78

