



| | |
|--------|------------------------|
| 品番 | LZY-93032XW+LZA-93035L |
| 光源 | LED 48W 2700K |
| 定格光束 | 4600 lm |
| 1/2照度角 | A-A' 66° B-B' 63° |
| ビーム角 | A-A' 114° B-B' 104° |

| | |
|------------------------|----------------------------|
| 器具効率 | 100.0 % |
| 上方光束 | 8.3 % |
| 下方光束 | 91.7 % |
| 器具間隔 最大限 (取付高さH) | A 1.29 H B 1.23 H |
| 保守率 | 良 0.69 中 0.67 否 0.63 |

| 反射率 (%) | 天井 | | | 壁 | | | 床 | | | 天井 | | | 壁 | | | 床 | | | |
|---------|------------------|----|----|-----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|----|
| | 80 | 70 | 50 | 50 | 30 | 10 | 50 | 30 | 10 | 80 | 70 | 50 | 50 | 30 | 10 | 50 | 30 | 10 | |
| 室指数 | 照 明 率 (× 0.01) | | | | | | | | | | | | | | | | | | |
| 0.6 | 45 | 37 | 31 | 44 | 36 | 31 | 42 | 35 | 30 | 41 | 34 | 30 | 41 | 34 | 30 | 41 | 34 | 30 | 41 |
| 0.8 | 55 | 46 | 40 | 54 | 46 | 40 | 51 | 44 | 39 | 49 | 43 | 38 | 49 | 43 | 38 | 49 | 43 | 38 | 49 |
| 1 | 63 | 54 | 48 | 62 | 53 | 47 | 59 | 51 | 46 | 56 | 50 | 45 | 56 | 50 | 45 | 56 | 50 | 45 | 56 |
| 1.25 | 71 | 62 | 56 | 69 | 61 | 55 | 65 | 59 | 53 | 62 | 56 | 52 | 62 | 56 | 52 | 62 | 56 | 52 | 62 |
| 1.5 | 77 | 69 | 62 | 75 | 67 | 61 | 71 | 64 | 59 | 67 | 62 | 57 | 67 | 62 | 57 | 67 | 62 | 57 | 67 |
| 2 | 85 | 78 | 72 | 83 | 76 | 71 | 78 | 73 | 68 | 74 | 70 | 66 | 74 | 70 | 66 | 74 | 70 | 66 | 74 |
| 2.5 | 91 | 84 | 79 | 88 | 82 | 77 | 83 | 79 | 74 | 79 | 75 | 71 | 79 | 75 | 71 | 79 | 75 | 71 | 79 |
| 3 | 95 | 89 | 84 | 92 | 87 | 82 | 87 | 83 | 79 | 82 | 79 | 76 | 82 | 79 | 76 | 82 | 79 | 76 | 82 |
| 4 | 100 | 95 | 91 | 97 | 93 | 89 | 92 | 88 | 85 | 86 | 84 | 81 | 86 | 84 | 81 | 86 | 84 | 81 | 86 |
| 5 | 103 | 99 | 95 | 100 | 96 | 93 | 94 | 91 | 89 | 89 | 87 | 84 | 89 | 87 | 84 | 89 | 87 | 84 | 89 |

