

姿図



品番	LZD-93124DWW+LZA-93013
光源	LED 15.2W Q+4000K
定格光束	770 lm
1/2照度角	30°
ビーム角	32°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.54 H B
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井			壁			50			30			0		
	80	70	50	50	30	10	50	30	10	50	30	10	50	30	10
床	20			20			20			20			0		
室指数	照 明 率 (× 0.01)														
0.6	82	78	75	82	78	75	81	77	74	80	77	74	73		
0.8	88	83	80	87	83	80	86	82	79	85	82	79	77		
1	94	89	86	93	89	85	91	88	85	90	86	84	82		
1.25	98	94	91	97	93	90	95	92	89	93	90	88	86		
1.5	101	97	94	100	96	93	98	95	92	96	93	91	88		
2	106	103	100	105	102	99	102	100	98	99	97	96	93		
2.5	110	107	105	108	106	103	105	103	101	102	100	99	96		
3	112	110	108	110	108	107	107	105	104	104	103	102	98		
4	114	113	111	113	111	110	109	108	107	105	105	104	100		
5	116	115	113	114	113	112	110	109	108	106	106	105	101		

