


## 姿図



品 番

LZW-90633XB+LZA-93096LBM

光 源

DECO-S Lite 4.3W 2700K M

定格光束

475 lm

1/2照度角

23°

ビーム角

24°

|                         |                            |
|-------------------------|----------------------------|
| 器具効率                    | 84.0 %                     |
| 上方光束                    | 0.0 %                      |
| 下方光束                    | 84.0 %                     |
| 器具間隔<br>最大限<br>(取付高さ H) | A 0.41 H<br>B              |
| 保 守 率                   | 良 0.69<br>中 0.67<br>否 0.63 |

| 反射率<br>(%) | 天井 | 80               |    |    | 70 |    |    | 50 |    |    | 30 |    |    | 0  |
|------------|----|------------------|----|----|----|----|----|----|----|----|----|----|----|----|
|            | 壁  | 50               | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0  |
|            | 床  | 20               |    |    | 20 |    |    | 20 |    |    | 20 |    |    | 0  |
| 室指数        |    | 照 明 率 ( × 0.01 ) |    |    |    |    |    |    |    |    |    |    |    |    |
| 0.6        |    | 70               | 66 | 64 | 69 | 66 | 63 | 69 | 65 | 63 | 68 | 65 | 63 | 62 |
| 0.8        |    | 74               | 70 | 68 | 74 | 70 | 68 | 73 | 69 | 67 | 72 | 69 | 67 | 65 |
| 1          |    | 79               | 75 | 72 | 78 | 75 | 72 | 77 | 74 | 71 | 75 | 73 | 71 | 69 |
| 1.25       |    | 82               | 79 | 76 | 81 | 78 | 76 | 80 | 77 | 75 | 78 | 76 | 74 | 72 |
| 1.5        |    | 85               | 82 | 79 | 84 | 81 | 78 | 82 | 79 | 77 | 80 | 78 | 76 | 74 |
| 2          |    | 89               | 86 | 84 | 88 | 85 | 83 | 85 | 83 | 82 | 83 | 82 | 80 | 78 |
| 2.5        |    | 92               | 89 | 88 | 90 | 88 | 87 | 88 | 86 | 85 | 85 | 84 | 83 | 80 |
| 3          |    | 94               | 92 | 90 | 92 | 91 | 89 | 89 | 88 | 87 | 87 | 86 | 85 | 82 |
| 4          |    | 96               | 94 | 93 | 94 | 93 | 92 | 91 | 90 | 89 | 88 | 87 | 87 | 83 |
| 5          |    | 97               | 96 | 95 | 95 | 94 | 93 | 92 | 91 | 91 | 89 | 88 | 88 | 84 |

