


姿図



品 番	DSL-5446YB
光 源	LDF5L-H-GX53/500/B27K <DAIKO>
定格光束	500 lm
1/2照度角	63°
ビーム角	100°

器具効率	91.2 %
上方光束	0.0 %
下方光束	91.2 %
器具間隔 最大限 (取付高さH)	A 1.23 H B 1.23 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		45	37	32	44	37	32	43	37	32	42	36	32	30
0.8		54	46	41	53	46	41	52	45	41	50	45	40	38
1		62	54	49	61	54	48	59	53	48	57	52	47	45
1.25		69	62	56	68	61	56	65	60	55	63	58	54	52
1.5		74	67	62	73	66	61	70	65	60	68	63	59	57
2		82	76	71	80	75	70	77	73	69	75	71	68	64
2.5		87	82	77	85	80	76	82	78	75	79	76	73	69
3		90	86	82	89	84	81	85	82	79	82	79	77	73
4		95	91	88	93	89	86	89	86	84	86	84	81	77
5		97	94	91	95	92	90	92	89	87	88	86	84	80

