


姿図



品 番	DSL-5448WW
光 源	LDF7N-H-GX53/700/B50K <DAIKO>
定格光束	790 lm
1/2照度角	62°
ビーム角	100°

器具効率	90.1 %
上方光束	0.0 %
下方光束	90.1 %
器具間隔 最大限 (取付高さ H)	A 1.21 H B 1.21 H
保 守 率	良 0.67 中 0.63 否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		44	37	32	44	37	32	43	36	32	42	36	32	30
0.8		54	46	41	53	46	40	51	45	40	50	44	40	38
1		61	54	48	60	53	48	58	52	47	57	51	47	45
1.25		68	61	55	67	60	55	65	59	54	63	58	54	51
1.5		73	67	61	72	66	61	70	64	60	67	63	59	56
2		81	75	70	79	74	70	77	72	68	74	70	67	64
2.5		86	81	76	84	80	75	81	77	74	78	75	72	69
3		89	85	81	88	84	80	84	81	78	81	79	76	72
4		94	90	87	92	88	85	88	85	83	85	83	81	77
5		96	93	90	94	91	89	91	88	86	87	85	84	79

