


姿図



品番	DDL-5445AWG
光源	LED5W 3500K
定格光束	445 lm
1/2照度角	27°
ビーム角	28°

器具効率	100.5 %
上方光束	0.0 %
下方光束	100.5 %
器具間隔 最大限 (取付高さH)	A 0.47 H B 0.47 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井				70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床				20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	84	79	76	83	79	76	82	78	76	81	78	75	74	
0.8	89	84	81	88	84	81	87	83	80	86	83	80	78	
1	94	90	87	93	89	86	92	88	86	90	87	85	83	
1.25	99	94	91	97	94	91	95	92	90	94	91	89	87	
1.5	102	98	95	100	97	94	98	95	93	96	94	92	89	
2	107	103	101	105	102	100	102	100	98	100	98	96	93	
2.5	110	107	105	108	106	104	105	103	102	102	101	99	96	
3	112	110	108	110	109	107	107	106	104	104	103	102	98	
4	115	113	112	113	111	110	109	108	107	106	105	104	100	
5	116	115	114	114	113	112	110	109	109	106	106	105	101	

