


姿図



品番	LLS-7120LUW+LLA-7125U
光源	LED 5.7W 2700K
定格光束	240 lm
1/2照度角	(A15° A' 18° ) B-B' 34°
ビーム角	(A16° A' 20° ) B-B' 36°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A *** H B 0.62 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井				70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床				20			20			20			0
室指数	照 明 率 ( × 0.01 )													
0.6	83	78	75	82	78	75	81	78	75	80	77	75	73	
0.8	88	84	80	88	83	80	86	82	80	85	82	79	78	
1	94	89	86	93	89	86	91	88	85	89	86	84	82	
1.25	98	94	90	97	93	90	95	91	89	93	90	88	86	
1.5	101	97	94	100	96	93	97	94	92	95	93	91	88	
2	106	103	100	104	101	99	102	99	97	99	97	95	92	
2.5	109	106	104	107	105	103	104	102	101	102	100	99	95	
3	111	109	107	110	108	106	106	105	104	103	102	101	97	
4	114	112	111	112	110	109	108	107	106	105	104	103	99	
5	115	114	113	113	112	111	109	108	108	106	105	105	100	

