


姿図



品番	DSL-4708YB
光源	LED 9.1W 2700K
定格光束	465.0 lm
1/2照度角	61°
ビーム角	84°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.17 H B 1.17 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井				70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床				20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	64	57	53	63	57	53	62	56	52	61	56	52	50	
0.8	73	67	62	73	66	62	71	66	61	70	65	61	59	
1	81	75	70	80	74	70	78	73	69	77	72	69	66	
1.25	88	82	78	87	81	77	85	80	76	83	79	75	73	
1.5	93	87	83	91	86	82	89	85	81	87	83	80	77	
2	99	95	91	98	94	90	95	92	89	92	89	87	84	
2.5	104	100	96	102	98	95	99	96	93	96	93	91	88	
3	106	103	100	105	101	99	101	99	96	98	96	94	90	
4	109	107	104	107	105	103	104	102	100	100	98	97	93	
5	111	109	107	109	107	105	105	103	102	101	100	99	94	

