


姿図



| | |
|--------|----------------|
| 品番 | DSL-4707YW |
| 光源 | LED 9.1W 2700K |
| 定格光束 | 620.0 lm |
| 1/2照度角 | 63° |
| ビーム角 | 88° |

| | |
|------------------------|----------------------|
| 器具効率 | 100.0 % |
| 上方光束 | 0.2 % |
| 下方光束 | 99.8 % |
| 器具間隔 最大限 (取付高さH) | A 1.21 H B 1.21 H |
| 保守率 | 良 0.67 |
| | 中 0.63 |
| | 否 0.56 |

| 反射率 (%) | 天井 | | | | 70 | | | 50 | | | 30 | | | 0 |
|---------|------------------|-----|-----|-----|-----|-----|-----|-----|----|----|----|----|----|---|
| | 壁 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| | 床 | | | | 20 | | | 20 | | | 20 | | | 0 |
| 室指数 | 照 明 率 (× 0.01) | | | | | | | | | | | | | |
| 0.6 | 58 | 51 | 46 | 57 | 50 | 46 | 56 | 50 | 45 | 55 | 49 | 45 | 43 | |
| 0.8 | 67 | 60 | 55 | 67 | 60 | 55 | 65 | 59 | 54 | 63 | 58 | 54 | 52 | |
| 1 | 75 | 68 | 63 | 74 | 68 | 63 | 72 | 66 | 62 | 71 | 65 | 61 | 59 | |
| 1.25 | 82 | 76 | 70 | 81 | 75 | 70 | 79 | 73 | 69 | 77 | 72 | 68 | 66 | |
| 1.5 | 88 | 81 | 76 | 86 | 80 | 76 | 84 | 79 | 75 | 81 | 77 | 73 | 71 | |
| 2 | 95 | 90 | 85 | 93 | 88 | 84 | 90 | 86 | 83 | 88 | 84 | 81 | 78 | |
| 2.5 | 100 | 95 | 91 | 98 | 94 | 90 | 95 | 91 | 88 | 91 | 89 | 86 | 82 | |
| 3 | 103 | 99 | 95 | 101 | 97 | 94 | 98 | 94 | 92 | 94 | 92 | 89 | 85 | |
| 4 | 107 | 103 | 100 | 105 | 102 | 99 | 101 | 98 | 96 | 97 | 95 | 93 | 89 | |
| 5 | 109 | 106 | 103 | 107 | 104 | 102 | 103 | 101 | 99 | 99 | 97 | 96 | 91 | |

