


姿図



品番	DDL-3874YW
光源	LDA4L-H-E17 <DAIKO>
定格光束	440 lm
1/2照度角	73°
ビーム角	116°

器具効率	68.6 %
上方光束	0.0 %
下方光束	68.6 %
器具間隔 最大限 (取付高さH)	A 1.49 H
	B 1.49 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井			壁			床			室指数			照明率 (×0.01)							
	80	70	50	30	10	50	30	10	50	30	10	50	30	10	0					
	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0				
	20			20			20			20			0							
	0.6	0.8	1	1.25	1.5	2	2.5	3	4	5	0.6	0.8	1	1.25	1.5	2	2.5	3	4	5
	32	39	45	51	55	61	64	67	71	73	32	39	45	51	55	61	64	67	71	73
	27	33	39	45	49	56	60	64	69	70	26	33	39	44	49	55	59	63	66	69
	23	29	35	41	45	52	57	60	64	67	23	29	35	40	45	52	56	60	64	67
	32	39	44	50	54	59	63	66	69	71	31	38	43	48	52	57	61	63	66	68
	26	33	39	44	49	55	59	63	66	69	26	33	39	44	49	55	59	63	66	68
	23	29	35	40	45	52	57	60	64	67	23	29	35	40	45	52	56	60	64	67
	31	38	43	48	52	57	61	63	66	68	31	38	43	48	52	57	61	63	66	68
	26	33	39	44	49	55	59	63	66	69	26	33	39	44	49	55	59	63	66	69
	22	29	34	40	44	51	55	58	62	65	22	29	34	40	44	51	55	58	62	65
	30	36	42	46	50	55	59	61	64	66	30	36	42	46	50	55	59	61	64	66
	26	32	37	43	46	52	56	59	62	64	26	32	37	43	46	52	56	59	62	64
	22	29	34	39	43	50	54	57	60	63	22	29	34	39	43	50	54	57	60	63
	30	36	42	46	50	55	59	61	64	66	30	36	42	46	50	55	59	61	64	66
	26	32	37	43	46	52	56	59	62	64	26	32	37	43	46	52	56	59	62	64
	22	29	34	39	43	50	54	57	60	63	22	29	34	39	43	50	54	57	60	63

