


姿図



| | |
|--------|--------------------|
| 品番 | DSY-4884AW |
| 光源 | LED 4.2W 3500K |
| 定格光束 | 500 lm |
| 1/2照度角 | A-A' 62° B-B' 61° |
| ビーム角 | A-A' 102° B-B' 96° |

| | |
|------------------------|----------|
| 器具効率 | 100.0 % |
| 上方光束 | 8.0 % |
| 下方光束 | 92.0 % |
| 器具間隔 最大限 (取付高さH) | A 1.21 H |
| | B 1.18 H |
| 保守率 | 良 0.69 |
| | 中 0.67 |
| | 否 0.63 |

| 反射率 (%) | 天井 | 80 | | | 70 | | | 50 | | | 30 | | | 0 |
|---------|----|------------------|----|----|-----|----|----|----|----|----|----|----|----|----|
| | 壁 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 |
| | 床 | 20 | | | 20 | | | 20 | | | 20 | | | 0 |
| 室指数 | | 照 明 率 (× 0.01) | | | | | | | | | | | | |
| 0.6 | | 47 | 38 | 33 | 46 | 38 | 33 | 44 | 37 | 32 | 42 | 36 | 31 | 29 |
| 0.8 | | 56 | 48 | 42 | 55 | 47 | 41 | 52 | 45 | 40 | 50 | 44 | 39 | 36 |
| 1 | | 64 | 55 | 49 | 62 | 55 | 49 | 60 | 53 | 47 | 57 | 51 | 46 | 43 |
| 1.25 | | 72 | 63 | 57 | 70 | 62 | 56 | 66 | 60 | 54 | 63 | 57 | 53 | 49 |
| 1.5 | | 77 | 69 | 63 | 75 | 68 | 62 | 71 | 65 | 60 | 68 | 63 | 58 | 54 |
| 2 | | 85 | 78 | 73 | 83 | 77 | 71 | 79 | 73 | 69 | 75 | 70 | 66 | 62 |
| 2.5 | | 91 | 85 | 79 | 88 | 83 | 78 | 84 | 79 | 75 | 79 | 75 | 72 | 67 |
| 3 | | 95 | 89 | 84 | 92 | 87 | 83 | 87 | 83 | 79 | 83 | 79 | 76 | 70 |
| 4 | | 100 | 95 | 91 | 97 | 93 | 89 | 91 | 88 | 85 | 86 | 84 | 81 | 75 |
| 5 | | 103 | 99 | 95 | 100 | 96 | 93 | 94 | 91 | 88 | 89 | 87 | 84 | 78 |

A-A'

B-B'

