


姿図



品 番

DDL-4764YW

光 源

LDA7L-G/60W/B27K <DAIKO>

定格光束

810 lm

1/2照度角

58°

ビーム角

80°

器具効率		51.4 %
上方光束		0.0 %
下方光束		51.4 %
器具間隔 最大限 (取付高さH)	A	1.11 H
	B	1.11 H
保 守 率	良	0.69
	中	0.67
	否	0.63

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6		29	25	22	28	25	22	28	24	22	27	24	22	21
0.8		34	30	27	33	29	27	32	29	27	32	29	26	25
1		38	34	31	37	34	31	36	33	31	35	32	30	29
1.25		41	38	35	41	37	35	40	37	34	38	36	34	33
1.5		44	41	38	43	40	38	42	39	37	41	39	37	35
2		48	45	43	47	45	42	46	43	41	44	42	41	39
2.5		51	48	46	50	47	45	48	46	44	46	45	43	41
3		52	50	48	51	49	48	50	48	46	48	47	45	43
4		54	53	51	53	52	50	51	50	49	50	48	47	45
5		56	54	53	55	53	52	52	51	50	51	50	49	46

