


姿図



品番	DDL-8789WW
光源	LED 4.6W 5000K
定格光束	390.0 lm
1/2照度角	59°
ビーム角	84°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.14 H
	B 1.14 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井			壁			50			30			0		
	80	70	50	30	10	50	30	10	50	30	10	50	30	10	0
床	20			20			20			20			0		
室指数	照 明 率 (× 0.01)														
0.6	59	52	47	59	52	47	57	51	47	56	51	47	45		
0.8	69	62	57	68	62	57	67	61	56	65	60	56	54		
1	77	70	65	76	70	65	74	69	64	73	68	64	62		
1.25	84	78	73	83	77	73	81	76	72	79	74	71	68		
1.5	90	84	79	88	83	78	86	81	77	83	79	76	73		
2	97	92	88	95	91	87	92	88	85	90	86	84	80		
2.5	101	97	93	100	96	92	96	93	90	93	91	88	85		
3	105	101	97	103	99	96	99	96	94	96	94	92	88		
4	108	105	102	106	103	101	102	100	98	99	97	95	91		
5	110	107	105	108	105	103	104	102	100	100	99	97	92		

