


姿図



品番	DSL-4708YW
光源	LED 9.1W 2700K
定格光束	620.0 lm
1/2照度角	63°
ビーム角	88°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 1.21 H
	B 1.21 H
保守率	良 0.67
	中 0.63
	否 0.56

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数		照 明 率 (× 0.01)												
0.6	58	51	46	57	50	46	56	50	45	55	49	45	43	
0.8	67	60	55	67	60	55	65	59	54	63	58	54	52	
1	75	68	63	74	68	63	72	66	62	71	65	61	59	
1.25	82	76	70	81	75	70	79	73	69	77	72	68	66	
1.5	88	81	76	86	80	76	84	79	75	81	77	73	71	
2	95	90	85	93	88	84	90	86	83	88	84	81	78	
2.5	100	95	91	98	94	90	95	91	88	91	89	86	82	
3	103	99	95	101	97	94	98	94	92	94	92	89	85	
4	107	103	100	105	102	99	101	98	96	97	95	93	89	
5	109	106	103	107	104	102	103	101	99	99	97	96	91	

