


姿図



品 番	DSL-4458YW
光 源	LDA7L-G/60W/B27K <DAIKO>
定格光束	810.0 lm
1/2照度角	64°
ビーム角	96°

器具効率	85.8 %		反射率 (%)	天井	80			70			50			30			0
	上方光束	24.5 %		壁	50	30	10	50	30	10	50	30	10	50	30	10	0
				床	20			20			20			20			0
下方光束	61.4 %		室指数	照 明 率 (× 0.01)													
器具間隔 最大限 (取付高さH)	A	1.24 H	0.6	36	29	25	35	28	24	32	26	22	29	24	21	18	
			0.8	44	36	31	42	35	30	38	32	28	34	29	26	22	
	B	1.24 H	1	50	42	37	47	40	35	43	37	33	39	34	30	25	
			1.25	56	48	43	53	46	41	48	42	38	43	38	35	29	
保 守 率	良 中 否	0.67 0.63 0.56	1.5	60	53	47	57	51	45	51	46	42	46	42	38	32	
			2	67	60	55	63	57	53	57	52	48	51	47	44	37	
			2.5	71	65	60	68	62	58	61	56	53	54	51	48	40	
			3	75	69	64	71	66	62	63	59	56	57	54	51	43	
			4	79	74	70	75	71	67	67	64	61	60	57	55	46	
			5	82	78	74	77	74	70	69	66	64	62	60	57	48	

